




QUALITY CONTROL SOLUTION

Fully integrated
Radio-HPLC
for quality control of
radiopharmaceuticals.

Fully integrated HPLC configuration for radiopharmaceutical analysis: For research and GMP-compliant quality control.

The Quality Control Solution radio-HPLC is a state-of-the art configuration for the analysis of radiolabeled targeting molecules according to Ph. Eur./USP standards. With an integrated quaternary HPLC pump, UV/VIS and radio detectors, together with the latest Chromstar workstation, the Quality Control Solution is a first-in-class radio-HPLC technology in an extremely compact design.

The central unit is equipped with a heating section and a fully shielded column as well as a fully shielded gamma detector. These features provide excellent reproducibility and simplified handling of radioactivity according to ALARA principle.



- The integration of only high quality materials and components allow for reliable and reproducible radioanalysis.
- 2 inch gamma detector is a key element of the radio-HPLC. In order to reach high efficient gamma ray detection, the measurement loop is surrounded by the NaI crystal.
- Set of inlets on the front panel allow to easily switching to different measurement loops (5, 20 and 50 µl) depending on the sensitivity required.

Together with the radio-HPLC, we provide our extensive expertise in the field of radiopharmaceutical manufacturing. Additionally we offer a full installation, qualification and service package. Our service includes personalized hands-on training, troubleshooting and maintenance, along with method optimization and validation. In addition our standard delivery already contains all components needed for full operation, such as glass bottles for solvents, filters, RP-column, tubings and important spare

parts including the tools and micro syringe for manual injection.

Upon request, the standard configuration can be upgraded or modified according to your specific requirements (e.g. autosampler, column switching valve, different detectors Photo-Diode Array, Refractive Index Detector, Conductivity Detector).



KEY ADVANTAGES

- Stand alone, fully integrated system
- Half-life correction
- Built-in, fully shielded radiodetector and column
- Adjustable sensitivity for different radioisotopes
- Additional modules for customization



Quality Control
Solution with an
Autosampler and
PDA Detector



Get all components
and services
from one supplier!



Radioisotopes + Targeting Molecules



iQS-Theranostics Synthesizer



Quality Control Solution



iQS® Ga-68 Fluidic Labeling Module



Reagent Sets + Cassettes



PASSION FOR PRECISION

S 1125 HPLC PUMP SYSTEM	
Material	Stainless steel/PEEK*, Tefl. on AF®, PVDF, ceramics, sapphire, ruby
Flow rate	Adjustable Micro: 0.001 – 2.000 ml/min Analytical: 0.001 – 10.000 ml/min
Flow accuracy	± 1.0 % 1.000 ml/min
Flow precision	± 0.1 % RSD 1.000 ml/min
Pressure range	0 – 40 MPa (0 – 6000 PSI)
Pressure pulsation	Typically < 0.1 MPa or < 1.0 %
Compressibility compensation	Integrated
Dimensions	310 x 165 x 478 mm
Weight	11 kg
Power supply	100 – 250 ~V (47 – 63 Hz)

* Depending on design

S 3245 UV/ VIS DETECTOR	
Material	Stainless steel/PEEK*
Baseline noise	± 1 x 10 ⁻⁵ AU (@240 nm, 1 sec risetime)
Baseline drift	2 x 10 ⁻⁴ AU / h
Wavelength range	190 – 900 nm
Wavelength accuracy	± 2 nm
Linearity	> 2.0 AU
Light source	Deuterium lamp, tungsten lamp
Wavelength program	Adjustable in 10 steps
Analogue output	1 x 1 V (optional: 2 x 1 V)
Additional features	Peak detector with +24 V switch contact for magnetic valve
Dimensions	396 x 165 x 478 mm
Weight	11 kg
Power supply	100 – 250 ~V (47 – 63 Hz)

* Depending on configuration

S 3700 -DETECTOR UNIT	
Half-life correction	Online correction
Material	PEEK; PFA
Detector	2 x 2" NaI(Tl) pinhole
Shielding	40 mm Pb equivalent
Energy range	0.02 – 1.2 MeV
Background noise	40 cpm
Dynamic range	0 – 400.000 cps
Flow cells	Variable 5, 20 and 50 µl by fitting setting
Column cabinet	Integrated with lead shielding 25 mm Pb-equivalent
Injection valve	Integrated
Data output	Digital, pulse counting
Column selction valve	Optional
Weight	38 kg
Dimensions	396 x 165 x 478 mm
Power supply	100 – 250 V (47 – 63 Hz)
Column oven	up to 70°C, fully shielded

About the ITM Group

ITM, a leading radiopharmaceutical biotech company, is dedicated to providing a new generation of radiomolecular precision therapeutics and diagnostics for hard-to-treat tumors. We aim to meet the needs of cancer patients, clinicians and our partners through excellence in development, production and global supply. With improved patient benefit as the driving principle for all we do, ITM advances a broad precision oncology pipeline, including two phase III studies, combining the company's high-quality radioisotopes with a range of targeting molecules. By leveraging our nearly two decades of pioneering radiopharma expertise, central industry position and established global network, ITM strives to provide patients with more effective targeted treatment to improve clinical outcome and quality of life.

Our contact

Phone: +49 89 329 8986-6000
Email: sales@itm-radiopharma.com
Web: www.itm-radiopharma.com

Distributed by ITM Pharma Solutions GmbH
Lichtenbergstrasse 1
85748 Garching/Munich, Germany

